

HP60i - CEILING & WALL DRYING PACKAGE



SPECS

Total System Airflow	108 CFM (cubic feet per minute)
Static Pressure (maximum)	60" of water lift
Weight (blower unit only)	50 lbs
Air Injector Hole	3/16" for wall & 1/4" for cabinet
Capacity	110 linear feet as packaged
Power Draw (115V)	5.6A -11A (depending on load)
Drying Modes	Negatively or positively
Dimensions	18" x 13" x 16.2" (with pipes)
Warranty	7 YR-Housing, 3 YR-Blower, 1 YR-Parts Limited

ORDER #
INJ01i

The HP60i Package is designed specifically for drying walls and ceilings using our patented Active Hoseline. Increase your systems' capabilities by purchasing Vac -It Panels

COMES WITH:	QTY	PART #
HP60 Unit	1	
Main AIR IN - Quick Connects installed at factory	1	PTFC
Main AIR OUT - Quick Connects installed at factory	1	PTMA
Carry Bag	1	CB1
Rolling Duffle Bag	1	CB2
Active Hoselines - 6' w/ 10 air ports each (2 Hosecuffs & 1 QC-Hose Connector)	12	AH3
AIR OUT Main Hose - 6' w/factory-set PRV	1	AOMH
AIR IN Main Hose - 6' w/ inline filter, factory-set PRV & Main QCT	1	AIMH
Quick Connect - Manifolds	10	QCM01
Quick Connect - Hose Connectors	3	QCC01
Quick Connect - Small T's	2	QCT01
Hosecuffs	10	HC3
End Cap Plugs	4	QCEPO1
Tubing Connectors	50	RHO7A
Soft Tubing Stoppers (bag of 50)	1	RP1
Wall Injectors	170	IMO6A
Safety Yellow Blank Hose (1½" x 50')	1	PLO3
Safety Yellow Tubing (3/8" x 200')	2	RH05A
Silencer	1	Sillencer
Manual & CD	1	

HP60i - CEILING & WALL DRYING EXAMPLES



Ceiling and wall dryouts using the INJ01i with patented Active Hoseline (tubing can be cut to the length needed for the job)



INJ01i drying walls through 1/4" easy to repair holes in baseboard in order to save wallpaper



Wall drying behind tile